



## OT-AC-7000 - Eisberg

- portable air conditioner -

The portable air conditioner OT-AC-7000 can be used nearly anywhere thanks to its compact design, e.g. in the office, in the living room at home or in the gym.

The air conditioner is ready to use and undemanding regarding the choice of location thanks to the four rollers and the flexible exhaust hose. It only needs a socket and a window for the exhaust air.

The system offers an optimal cooling performance for rooms of up to 70 m<sup>3</sup> and a circulating flow rate of up to 300 m<sup>3</sup>/h.

You can easily operate the device with its user-friendly membrane key control panel at the top of the system or via the included infrared remote control.

Furthermore the portable air conditioner has numerous functions and features, such as a timer and sleep function, a cooling, fan and dehumidification mode, an easy to clean and removable air filter and an adjustable blow-out direction.

## Technical specification - OT-AC-7000

Energy labelling:

Cooling capacity max.:

Range of use:

Operating tenperature max.:

Sound level:

Refrigerant:

Refrigerant charge: Dehumidify capacity max.:

Air circulation max .:

EER value (Energy Efficiency Ratio):

Input supply voltage:

Rated current:

Rated input max.: Suction:

Discharge:

Max. allowable pressure:

Protection functions:

2.05 kW / 7000 BTU/h

ca. 70 m<sup>3</sup>

7-35 °C (44-95 °F)

ca. 60 dB(A)

R290  $0.13 \, \text{kg}$ 17 I / day

300 m<sup>3</sup>/h 2.61

220-240 V, 50 Hz

3.4 A 0.792 kW 0,6 MPa 1,8 MPa

3.0 MPa

frost protection function

overflow protection function compressor protection function

defrosting function

Exhaust hose (length/diameter): ca. 150 / 14 cm 67,8 x 32,8 x 30,5 cm Dimensions (h x w x d): 21 / 23 kg Weight (product/overall): Barcode: 792742176104

OT-AC-7000 Manufacturer code:

Mark of conformity: CE

