

## OT-EC-1200 - Eisblower

## - portable evaporative cooler -

The portable evaporative cooler OT-EC-1200 can be used nearly anywhere thanks to its compact design, e.g. in the office, in the living room at home or in the gym.

The evaporative cooler is ready to use and undemanding regarding the choice of location thanks to the four rollers. It only needs a socket.

The system offers an optimal cooling performance for rooms of up to 72 m³ and an air flow rate of up to 1200 m³/h.

You can easily operate the device with its user-friendly membrane key control panel at the top of the system or via the included infrared remote control.

Furthermore the portable evaporative cooler has numerous functions and features, such as a timer function, an ionisator mode, an adjustable fan speed and blow-out direction.



## Technical specification - OT-EC-1200

Range of use: ca. 70 m³ / 30 m² Fan speed: 425-1050 rpm Wind speed: 2,8-8,2 m/s Air flow rate max.: 1200 m³/h (705 cf

Air flow rate max.: 1200 m³/h (705 cft)
Sound level: ca. <70 dB(A)
Input supply voltage: 220-240 V, 50 Hz

Power consumption: 40-130 W

(0,17-0,56 kW/h)

Water tank capacity: 10,8 I
Water tank detachable: yes
Fan diameter: 20,8 cm

Dimensions (h x w x d): 92 x 38 x 31 cm

Cooling pad (#5090): 334 x 237 x 35 mm

Weight (product/overall): 9,3 / 11,3 kg

Barcode: 792742176111 Manufacturer code: OT-EC-1200

Mark of conformity: CE



